
Stellar

Item # P3T-60120 - P3T-60140 (21 colorways)







PHYSICAL PROPERTIES

Width Trim to 48" Packaging 15-vd rolls **Thickness** 0.033

Heavy Polyester/ Cotton knit Backing

N/A Repeat

Reverse hang, Random match Installation Fire Safety Class "A" rated ASTM E-84

ENVIRONMENTAL & HEALTH

Indoor Air Meets California Section 01350

Fungal Resistant ASTM G-21 Bacterial Resistant ASTM G-22 **HPD** third-party certified **EPD** third-party certified

NSF/ANSI 342 third-party certified, ask distributor for details

Recycled content

California Prop 65, no labeling required

Non-phthalate



Impact Resistance ASTM D- 5420-10 Gardner Method

Pattern In-Lbs Stellar 88

A Chemical

Chemical Resistance ASTM D-1308

Spot test covered 3.1.1

Cleaning Agents Tide w/H20

Virex Mustard Black Sharpie Ammonia Isopropyl Alcohol Ink Pen Goof Off **Betadine** Fantastik Shoe Polish Lvsol Lipstick Hydrogen Peroxide

Black Rubber Brake Fluid Bleach Methyl Ethyl Ketone Spray Paint

Results: No change in P3TEC

surface from exposure to these agents.

above was wiped clean with at least one listed cleaning

Results: Each staining agent

Cleaning

ASTM F-793

SECTION 7.5

Staining Agents

Grape Juice

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process. See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)

Abrasion

Abrasion Resistance ASTM D- 4060-14 Taber Method

Test Spec CS-10F wheel

500 gram load @200 cycles

Weight loss: 0.02%