Tranquility

Item # P3T-60025 - P3T-60042 (18 colorways)







PHYSICAL PROPERTIES

Width Trim to 48" Packaging 15-yd rolls 0.032 **Thickness**

Backing Heavy Polyester/ Cotton knit

Repeat

Installation Reverse hang, Random match Fire Safety Class "A" rated ASTM E-84

ENVIRONMENTAL & HEALTH

Indoor Air Meets California Section 01350

Fungal Resistant ASTM G-21 Bacterial Resistant ASTM G-22 HPD third-party certified **EPD** third-party certified

NSF/ANSI 342 third-party certified, ask distributor for details

Recycled content

California Prop 65, no labeling required

Non-phthalate

Impact

Impact Resistance ASTM D- 5420-10 Gardner Method

Pattern In-Lbs Tranquility 88

Chemical

Chemical Resistance Cleaning ASTM D-1308 ASTM F-793 Spot test covered 3.1.1 SECTION 7.5

Cleaning Agents Tide w/H20 Virex Ammonia Isopropyl Alcohol Goof Off Fantastik Lysol

Results: No change in P3TEC surface from exposure to

Hydrogen Peroxide

Methyl Ethyl Ketone

these agents.

Bleach

Results: Each staining agent above was wiped clean with at least one listed cleaning

agent.

Staining Agents

Grape Juice

Black Sharpie

Mustard

Ink Pen

Lipstick

Betadine

Shoe Polish

Black Rubber

Brake Fluid

Spray Paint

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process. See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)

Abrasion

Abrasion Resistance ASTM D- 4060-14 Taber Method

Test Spec CS-10F wheel

500 gram load @200 cycles

Weight loss: 0.02%